

SAMSUNG



Samsung CEBU R32

The Samsung CEBU wall mounted system cools rooms quickly from corner to corner, so you're always comfortable.

Auto Clean

The Auto Clean functionality enables cleaning of the heat exchangers anytime after you turn off the unit. This function automatically dries the Heat Exchanger using a 3 step process and prevents the build up of bacteria and odors. It can easily be enabled or disabled with the click of the remote controller.

Easy Filter Plus

Unlike conventional filters that may be difficult to access the Easy Filter Plus is located externally on the top of the unit. This means it can be easily removed and cleaned without needing to open a cover or pull hard on it. Thanks to the filter's dense mesh it's very effective at capturing dust and therefore keeping the Heat Exchanger clean and working efficiently. The special coating on the filter helps protect residents from certain airborne contaminants¹.

WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App². Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system³ analyses and predicts your needs so it can suggest the best settings for inside your home.


¹Tested in Korean test lab (FITI). Data has been measured under specific testing conditions and may vary depending on environmental factors and individual use. Certain airborne contaminants referred to are Escherichia coli ATCC 25922, Staphylococcus aureus ATCC 6538.

² Available on Android and iOS devices. A Wi-Fi connection and Samsung SmartThings account are required.

³ Voice control is supported in English.

Samsung CEBU R32

- AI Auto Comfort.
- Wi-Fi Control with Samsung SmartThings and Bixby voice controls.
- Compressor with Digital Inverter Boost technology.
- Equipped with NASA communication protocol.
- Direct drive fan powered by a BLDC motor.
- Triple Protector Plus to protect compressor, fin and controller from power surges.



Specifications

Model No.	Indoor Unit		AR09TXFYAWKXEU AR09TXFYAWKNEU	AR12TXFYAWKXEU AR12TXFYAWKNEU	AR18TXFYAWKXEU AR18TXFYAWKNEU	AR24TXFYAWKXEU AR24TXFYAWKNEU
Capacity	Cooling	kW	2.50(0.90-3.35)	3.50(0.90-4.0)	5.0(1.6-6.7)	6.0(1.4-7.6)
	Heating		3.20(0.90-4.50)	3.50(0.90-5.0)	6.0(1.30-8.0)	7.4(1.2-9.4)
UK Capacity	Sensible cooling	kW	2.31	2.69	3.88	5.50
Efficiency	EER		3.57	2.87	3.60	3.33
	COP ¹	W/W	3.81	3.72	3.53	3.15
	SEER ¹		6.7/ A++	6.5/ A++	6.8/ A++	6.4/ A++
	SCOP ¹	W/W	4.0/ A+	4.0/ A+	3.8/ A	3.8/ A
Annual Energy Consumption	Cooling	kWh/a	131	188	257	355
	Heating		735	770	1,400	1,511
Sound Pressure	Indoor (H/M/L)		37/19	38/19	41/25	45/26
	Outdoor (Cooling/Heating)	dB(A)	46	47	51	54
Sound Power	Indoor Unit	dB(A)	54	56	58	62
	Outdoor Unit		63	64	65	68
Airflow Rate	Indoor Cooling (H/M/L)	l/s	163/155/140	172/155/140	263/240/216.7	263/240/216.7
	Heating (H/M/L)	l/s	178/172/155	187/172/155	263/240/216.7	275/ 251.7/ 228.3
	Outdoor	l/s	467	467	833	833
Dimensions (W x H x D)	Indoor	mm	820 x 299 x 215	820 x 299 x 215	1,055 x 299 x 215	1,055 x 299 x 215
	Outdoor		660 x 475 x 242	660 x 475 x 242	880 x 638 x 310	880 x 638 x 310
Net Weight	Indoor Unit	kg	9.1	9.1	11.5	11.6
	Outdoor Unit		22.6	22.6	39.7	43.2
Refrigerant	Pipe Size Gas	ø, inch	3/8	3/8	1/2	5/8
	Liquid		1/4	1/4	1/4	1/4
	Std/Max Pipe Length (Height)	m	3/15(8)	3/15(8)	3/30(15)	3/30(15)
	Pre Charge to		5	5	5	5
	Factory Charging	kg	0.70	0.70	1.30	1.15
	Additional Charge	g/m	15	15	15	15
	CO ₂ Equivalent (R32 - GWP 675)	tCO ₂ e	0.47	0.47	0.88	0.78
Electrical	Power Supply	V, Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz
	Power Input Cooling		0.205/0.70/1.03	0.205/1.22/1.4	0.32 / 1.39 / 2.18	0.3 / 1.95 / 2.6
	Heating	kW	0.20/0.84/1.27	0.20/0.94/1.45	0.27 / 1.7 / 2.5	0.27 / 2.35 / 3.3
	Current Input Cooling	A	1.3/3.6/4.7	1.3/5.6/6.3	2 / 6.4 / 10	2 / 8.8 / 11.5
	Heating		1.4/4.0/5.6	1.4/4.5/6.4	1.7 / 7.8 / 11.5	1.7 / 10.5 / 14.5
	MCA	A	5.6	6.4	11.5	14.5
	MFA		16	16	20	20
	Interconnecting Communication Cable	mm ²	Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection			

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Accessory			
Wireless Remote Controller	Premium Wired Controller	Sub PCB to connect wired remote controller	Touch Controller
Included	MWR-WG00JN	MIM-A00N	MWR-SH11N

Copyright © 2020 Samsung Electronics Air Conditioner Europe B.V. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice and may include preliminary information. Non-metric weights and measurements are approximate. All data was deemed correct at the time of creation. Samsung is not liable for errors or omissions. Some images may be digitally altered. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognised and acknowledged.

Samsung Electronics Air Conditioner Europe B.V.
 Evert van de Beekstraat 310, 1118 CX Schiphol
 P.O. Box 75810, 1118 ZZ Schiphol
 The Netherlands
 +31 (0)8 81 41 61 00